

**CM-2000**



**Features:**

- 3½ Digits
- Non Contact Voltage (NCV)
- Clamp Torch
- Clamp Open: 28mm

**DC VOLTAGE**

Range	Resolution	Accuracy
200mV	0.1mV	±0.5% of rdg + 5 digits
2V	1mV	
20V	10mV	
200V	100mV	
600V	1V	±1.0% of rdg + 5 digits

**AC VOLTAGE**

Range	Resolution	Accuracy
200mV	0.1mV	± 1.5% of rdg + 10 digits
2V	1mV	± 1.0% of rdg + 5 digits
20V	10mV	
200V	100mV	
600V	1V	

**AC CURRENT**

Range	Resolution	Accuracy
2A	1mA	±3.0% of rdg + 5d digits
20A	10mA	±1.5% of rdg + 5d digits
200A	100mA	
600A	1A	

**RESISTANCE**

Range	Resolution	Accuracy
200Ω	0.1Ω	±0.8% of rdg + 5 digits
2kΩ	1Ω	±0.8% of rdg + 1 digits
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1KΩ	
20MΩ	10KΩ	±1.2% of rdg + 5 digits

**POWER**

AAA1.5V X 2

- Standard Accessories : Test Leads, Manual, Soft Carrying case
- Dimension : 230(H) x 80(W) x 37(D)mm

**CM-2007**



**Features:**

- 3¾ Digits
- Non Contact Voltage (NCV)
- Frequency, CAP, Temp.

**DC VOLTAGE**

Range	Resolution	Accuracy
400mV	0.1mV	±1.0% of rdg + 5 digits
4V	1mV	±0.5% of rdg + 5 digits
40V	10mV	
400V	100mV	
600V	1V	

**AC VOLTAGE**

Range	Resolution	Accuracy
400mV	0.1mV	± 1.5% of rdg + 5 digits
4V	1mV	± 1.0% of rdg + 5 digits
40V	10mV	
400V	100mV	
600V	1V	

**AC CURRENT**

Range	Resolution	Accuracy
400A	100mA	<40A ±3.0% of rdg + 5 digits
600A	1A	>40A ±2.0% of rdg + 5 digits

**RESISTANCE**

Range	Resolution	Accuracy
400Ω	0.1Ω	±0.8% of rdg + 5 digits
4kΩ	1Ω	±0.8% of rdg + 3 digits
40kΩ	10Ω	±1.2% of rdg + 5 digits
400kΩ	100Ω	
4MΩ	1KΩ	
40MΩ	10KΩ	

**CAPACITANCE**

Range	Resolution	Accuracy
4nF	1pF	±5.0% of rdg + 20 digits
40nF	10pF	±3.5% of rdg + 10 digits
400nF	100pF	
4μF	1nF	
40μF	10nF	
200μF	100nF	±5.0% of rdg + 10 digits

**FREQUENCY**

Range	Resolution	Accuracy
100Hz	0.1Hz	±0.5% of rdg + 5 digits
1kHz		
10kHz	1Hz	
100kHz	10Hz	
1MHz	100Hz	
10MHz	1kHz	

**TEMPERATURE**

Range	Resolution	Accuracy
(-40-750)°C	1°C	<400°C ±1.0% of rdg + 5 digits ≥400°C ±1.5% of rdg + 15 digits

**POWER**

AAA1.5V X 2

- Standard Accessories : Test lead, Manual, TP-04 Temperature Probe, Soft Carrying case
- Dimension : 230(H) x 80(W) x 37(D)mm

