

LX-101A/LX-102A



Features:

- DATA HOLD
- Auto Power Off (APO)
- PEAK HOLD (LX-102A)

LX-103



Features:

- Large Range up to 2,00,000 Lux
- Large LCD Display with back Light and Bar Graph
- Auto Power Off (APO)
- Max/Min and Data Hold

LX-104



Features:

- 4000 Counts with Bar graph 61 Segments
- User selectable FC/Lux
- USB Computer Interface (Advanced software program for all windows)
- Capacity of Data Logging 99

Technical Data

Basic Function		LX-101A	LX-102A	LX-103	LX-104
Range	Lux	0 - 2,00,000 LUX	0 - 2,00,000 LUX	0 - 2,00,000 LUX	4,00,000 LUX
	FC	-	0 - 20,000 FC	0 - 20,000 FC	-
Resolution		0.1 Lux		0.01 Lux/0.01 FC	
Accuracy		+ 5% of reading		3%	
Receiving Light		Silicon photo electricity diode		Silicon photo electricity diode	
Power		9V (6F22) X 1		9V (6F22) X 1	
Standard Accessories		Soft carrying case, Manual		Soft Carrying Case, Manual	
Dimension		Photo Detector : 82(H) x 55(W) x 7(D)mm Meter Body : 148(H) x 70(W) X 40(D)mm		170mm x 89mm x 43mm	
				Photo Detector : 115(H) x 60(W) x 27(D)mm Meter Body : 203(H) x 75(W) x 50(D)mm	