

SMPS-3002/SMPS-3005

Mini Series Switching Power Supply

Output Voltage	Output Current	Display	Accuracy
0-30V	0-2A	LED Digit Display	±1% of rdg ± 1 digits
0-30V	0-5A		

The power output parameters

Model	Voltage Stability	Current Stability	Load Regulation	Ripple And Noise
Mini Series	≤0.2%	≤0.8%	≤0.2%	≤0.1%

- Standard Accessories : Power Cord, Manual, Test Lead
- Dimension : 240 x 150 x 270mm



DC-3002/DC-3003/DC-3005/DC-3010

Features:

- Line Regulation : ≤0.01% +3mV
- Load Regulation : ≤0.001% +3mV
- Ripple and noise : ≤1mV rms
- Protection : Constant current and Short-circuit protection
- Indication Accuracy : ≤0.5% +1digit
- Input Voltage : 220 V AC ± 10%, 50Hz ± 2Hz

Models :

Model	DC 3002	DC 3003	DC 3005	DC 3010
O/P Voltage	0~30V			
O/p Current	0~2A	0~3A	0~5A	0~10A

- Standard Accessories : Power Cord, Manual, Test Lead
- Dimension : 120 x 150 x 270mm



DC-3002-II/DC-3003-II/DC-3005-II

Features:

- Line Regulation : CV ≤0.01% + 3mV ; * CC ≤0.2 % + 3 mA
- Load Regulation : CV ≤0.01% + 3mV ; * CC ≤0.2 % + 3 mA
- Ripple and Noise : CV ≤1mV rms ; * CV ≤3 mA rms
- Protection : Constant current and Short-circuit protection
- Tracking Error : ≤0.5% +10 mV
- Indication Accuracy : ≤0.5% +1digit
- Input Voltage : 220 V AC ± 10%, 50hz ± 2Hz

Models :

Model	DC 3002-II	DC 3003-II	DC 3005-II
O/P Voltage	0~30V		
O/p Current	0~2A	0~3A	0~5A
Fixed O/P	5V,2A		

- Standard Accessories : Power Cord, Manual, Test Lead
- Dimension : 240 x 150 x 270mm

